

# INSTALLATION GUIDELINES

## FLOOR REGISTERS



### **SMOOTH FLOORING- VIYNL, CERAMIC TILE, HARDWOOD**

- Hole cutout must be no larger than 1/16" inch on each side of the inserted flange
- Cutout dimension is 2 3/8" x 10"
- Secure product into opening using correct screws (flat head screws recommended)

### **CARPETED FLOORING**

- Hole cutout must be no larger than 1/16" inch on each side of the inserted flange
- Cutout dimension is 2 3/8" x 10"
- Remove or 'cut back' the padding a minimum of 2" each side from cutout dimension and secure register to the floor. This eliminates the 'give' of the padding and allows the register to draw down to the floor
- Failure to do this can cause the register to lift and 'flex up' and become a tripping hazard
- Secure product into opening using correct screws (flat head screws recommended)

### **CAUTION!!**

DO NOT OVERTIGHTEN OR ANGLE SCREWS DURING INSTALLATION!!!

### **IMPORTANT!!**

THE DESIGN OF THIS PRODUCT WAS INTENDED FOR SECURE ATTACHMENTS TO FLOORING WITHOUT FLEXING!!!

THIS PRODUCT IS PLASTIC AND WILL NOT PERFORM IN THE SAME MANNER AS A METAL PRODUCT WOULD. ADDITIONAL CARE IN INSTALLATION AND HANDLING MUST BE TAKEN!!!

FAILURE TO FOLLOW THESE INSTRUCTIONS FOR INSTALLATION OF OUR PRODUCT WILL FORFEIT ANY WARRANTY CONSIDERATION.

